


## BHE4TW ELECTRIC TORQUE PUMP

OIL CAPACITY: 5L  
 RATED FLOW: 0.8L/min  
 MAX. PRESSURE: 700Bar  
 POWER: 1.1KW  
 WEIGHT: 22kg



**TWIN HOSE**

Various length twin hose with quick couplers available.



**Manifold**

One to four tools manifold available for options.

### FEATURES AND BENEFITS

- Brushless motor, low maintenance.
- Two stage pump, more efficient.
- 75dB low noise.
- Inside safety valve, safe and reliable.
- High-protection weak power control handle
- With high accuracy adjustable relief valve to adjust system pressure.



Twin hose



BHE4TW-2



BHE4TW-4

Model	Rated Pressure	Voltage	Flow 1st Stage	Flow 2nd Stage	Oil Capacity	Power	Weight
	Bar		V	L/min			
<b>BHE4TW</b>	700	220	7	0.8	5	1.1	22

Remarks: Each BHE4TW pump can be equipped with 2, 3 or 4 ports manifold. When ordering, Customer can add number after the model for ports quantity. i.e: BHE4TW-4 is with 4 ports for 4 tools.

## BHE4TW/BHE5TW ELECTRIC TORQUE PUMP

OIL CAPACITY: 10L  
 RATED FLOW: 1L/min  
 MAX. PRESSURE: 700Bar  
 POWER: 1.5KW  
 WEIGHT: 35-40kg



### FEATURES AND BENEFITS

- Brushless motor, low maintenance.
- Two stage pump, more efficient.
- 75dB low noise.
- Inside safety valve, safe and reliable.
- High-protection weak power control handle
- With high accuracy adjustable relief valve to adjust system pressure.

Model	Rated Pressure	Voltage	Flow 1st Stage	Rated Flow	Oil Capacity	Power	Weight
	Bar		V	L/min			
<b>BHE5TW</b>	700	220	9	1	10	1.5	35

Remarks: Each BHE5TW pump can be equipped with 2, 3 or 4 ports manifold. When ordering, Customer can add number after the model for ports quantity. i.e: BHE5TW-4 is with 4 ports for 4 tools.



**TWIN HOSE**

Various length twin hose with quick couplers available.



**Manifold**

One to four tools manifold available for options.



**Lockable Wheel**

With lockable wheel, easy for moving.



BHE6TW

Model	Rated Pressure	Voltage	Flow 1st Stage	Rated Flow	Oil Capacity	Power	Weight
	Bar		V	L/min			
<b>BHE6TW</b>	700	380	9	1	10	1.5	40

Remarks: Each BHE6TW pump can be equipped with 2, 3 or 4 ports manifold. When ordering, Customer can add number after the model for ports quantity. i.e: BHE6TW-4 is with 4 ports for 4 tools.

## BETW-200FBP EXPLOSION-PROOF TORQUE PUMP

OIL CAPACITY: 10L  
 RATED FLOW: 0.8L/min  
 MAX. PRESSURE: 700Bar  
 POWER: 1.5KW  
 WEIGHT: 40kg



- Compact Design to minimize weight
- Explosion-proof motor, electric part and solenoid valve.
- Pressure regulating valve for easy adjust system pressure




- Remote control cable can be customized. Standard one is 6 meters long
- With oil cooler for long time working without high oil temperature
- Aluminum frame with wheels, convenient for moving and protecting the pump body
- Level gauge for supervision oil level in the tank



Twin Hose

- FEATURES AND BENEFITS**
- Three stages to release high efficiency of work
  - Drive 2 or 4 wrenches
  - Aluminum alloy reservoir for easy moving
  - Cooling fan for continuous work
  - Motor of different voltage available



Model	Max. Pressure bar	Voltage V	Flow@ 1st Stage L/min	Flow@ 2nd Stage L/min	Oil Capacity L	Motor KW	Weight kg
BETW-200FBP	700	380	8	0.8	10	1.5	40

## BETW-200 ELECTRIC TORQUE WRENCH PUMP

OIL CAPACITY: 8L  
 RATED FLOW: 0.8L/min  
 MAX. PRESSURE: 700Bar  
 POWER: 1.1KW  
 WEIGHT: 26.5kg



- Remote control cable can be customized. Standard one is 6 meters long
- HAWE solenoid valve control
- Pressure regulating valve for easy adjust system pressure

- Compact Design to minimize weight
- With oil cooler for long time working without high oil temperature
- Aluminum frame, convenient for handling and protecting the pump body




Optional 4 tools block

Level gauge for supervision oil level in the tank

- FEATURES AND BENEFITS**
- Three stages to release high efficiency of work
  - Drive 2 or 4 wrenches
  - Aluminum alloy reservoir for easy moving
  - Cooling fan for continuous work
  - Motor of different voltage available




TWIN HOSE



Model	Pressure Output Bar	Voltage V	Flow@ 1st Stage L/min	Flow@ 2nd Stage L/min	Flow@ 3rd Stage L/min	Oil Capacity L	Power KW	Weight KG
BETW-200	40-700	220	7	1.6	0.8	8	1.1	26.5

## BE-200Q AIR DRIVEN HYDRAULIC TORQUE PUMP

OIL CAPACITY: 8L  
 RATED FLOW: 0.8L/min  
 MAX. PRESSURE: 700Bar  
 WEIGHT: 20kg




Twin Hose

### FEATURES AND BENEFITS

- Solenoid valve control
- Outside pressure valve for easy adjusting
- Air outport, work in extreme environment
- Oil / mig segregation

### Parameters:

Power Source:	Air
Oil Capacity:	8L
Flow Rate:	7-1.6-0.8 L/MIN
Pressure output:	40-700 Bar
Air Pressure:	4-8 Bar
Efficiency:	1.1KW
Weight:	20.5KG



Model	Oil Capacity	Valve	Air Motor	Flow Rate L/min			Oil Port Out	Oil Port Return	Max. Pressure
	L			1	2	3			MPa
BE200Q	8	Solenoid	Speed 3000R/min, Power 1.1KW, Air Input 4-8Bar, Air consumption 1.9m³/min	7	1.6	0.8	NPT1/4	NPT1/4	70